

# Lynkobling

Type FFNB/P Passer til Multifaster



WALTERSCHEID

Str.	Norm. Flow l/min	Max arb.tryk Bar	Tilslut Ø A BSP	Leverandør kode		Gevind	Best. Nr. Hun	Best. Nr. Han	Rep. Sæt Han
				Hun	Han				
04 (1/4)	20	250	1/4"	2FNB14 GAS F	2FNP14 GAS M	Inv. BSP	8949260	8949261	89492487-1
04 (1/4)	20	250	1/4"	2FNB14-38SF	2FNP14-38SM	Inv. BSP	8079212	8079213	
06 (3/8)	40	250	3/8"	2FNB38 GAS F	2FNP38 GAS M	Inv. BSP	8949242	8949243	8949340-1
06 (3/8)	40	250	3/8"		<b>3FNP38 GAS M*</b>	Inv. BSP		<b>8075901</b>	
06 (3/8)	40	250	3/8" - 1/2"	2FNB38-12 GAS F	2FNP38-12 GAS M	Inv. BSP	8949240	8949241	8949340-1
06 (3/8)	40	250	3/8" - 22X1,5	2FNB38-2/22 F	2FNP38-2/22 M	Udv. G. M22 x 1,5	8949280	8949281	
08 (1/2)	70	250	1/2"	2FNB12 GAS F	2FNP12 GAS M	Inv. BSP	8949246	8949247	8949247-1
08 (1/2)	70	250	1/2"		<b>3FNP12GAS M*</b>	Inv. BSP		<b>8949270</b>	
08 (1/2)	70	250	1/2" - 22X1,5	2FNB12-2/22 F	2FNP12-2/22 M	Udv. G. M22 x 1,5	8949254	8949255	
08 (1/2)	70	250	1/2" - 24X1,5		2FNP12-3/24 M	Udv. G. M24 x 1,5	8073471	8949245	
12 (3/4)	125	250	3/4"	2FNB34 GAS F	2FNP34 GAS M	Inv. BSP	8949250	8949251	8949251-1
12 (3/4)	125	250	3/4"		<b>3FNP34GAS M*</b>	Inv. BSP		8076896	
12(3/4)	125	250	3/4" - 1"	2FNB34-1 GAS F	2FNP34-1 GAS M	Inv. BSP	8949252	8949253	8949252-1

\* 3FNP = Skifte under tryk, aflaster i han parten

\*\* GAS = BSP Gevind

\*\*\* F= Female - M = Male

Eksempel:

2FNB38 GAS F

Female = Hun delen - (Delen med håndtaget)

BSP Gevind

3/8" Gevind

Standard 2FNB kobling (Findes også i en 3FNP - Kan skiftes under tryk)

